



Mezzguard


Combine outstanding fire resistance with high light reflectance and balanced acoustical performance. Ideal for mezzanine floors, warehouses, and other large open workspaces.

Key Features

- Engineered for excellent fire resistance performance for fully loaded mezzanine floors
- Finely sanded surface texture with small pin holes for well-balanced acoustical performance
- With high light reflectance, these white tiles bounce natural light around a space, brightening mezzanine floors and reducing reliance on artificial light



Edge Detail Board



Thickness (mm)	16
Modules (mm)	600 x 600 2620M 1200 x 600 3066M
Suspension Systems	Prelude 24 XL ² / TLS
Colour	Global White

Sustainability

52

Acoustics



	α_w	D _{nfw}	Class	NRC	Hz α_p					
					125	250	500	1000	2000	4000
Board (16mm)	0.60	34 dB	C	0.55	0.50	0.45	0.55	0.60	0.65	0.60

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

UK 60 minutes BS 476: Part 21: 1987
For full details see assessment report WF 173816
Tested at 100% design load
Tested without hold down clips for applications where a ceiling is open to a larger full height space

Performances & Features



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email info@zentia.com

TDS 080.1.11.22